



Ocean Asia DB-550 RIB



SPECIFICATIONS

Length Overall:	_____ 18' 0.53"	5.50 m
Beam:	_____ 8' 4.39"	2.55 m
Internal Length:	_____ 15' 9"	4.80 m
Internal Beam:	_____ 4' 3.18"	1.30 m
Tube Diameter:	_____ 1'6" / 1'10"	45 / 55 cm
No. of Air Chambers:	_____ 5	
No. of Passengers:	_____ 10	
Fuel Capacity:	_____ 18.5 US Gal	70 litres
Engine Power Range:	_____ 40 hp to 115 hp	
CE Category:	_____ C	

Standard Equipment

- * Heavy-duty fiberglass deep-vee hull;
- * Heavy-duty stringer system laminated into hull;
- * Fiberglass Non-skid deck
- * Dual deck drains into bilge area;
- * Larger anchor locker in bow area, draining into bilge;
- * Rule, 500GPH automatic bilge pump;
- * Larger under-seat storage area with covers;
- * Splash well, draining;
- * Engine mounting plate
- * Swim/boarding platform;
- * Stainless steel lifting hooks & mooring cleat;
- * 70L S/S fuel tank;
- * S/S deck filter & vent for fuel;
- * WEMA Fuel level sensor & indicator;
- * Molded Fiberglass console;
- * Perspex windshield with S/S handrails;
- * Storage compartment with plastic door in console;
- * Waterproof switch panel with five circuit breakers;
- * 12V 120AH battery including battery switch;
- * Cushions in closed cell foam for fwd sunbathing;
- * Cushions in closed cell foam for all seating;
- * Heavy-duty PVC 1.2mm, 1000D inflatable tube;
- * 5 independent inflatable sections in tube;
- * 5 plastic non-corrosive 2-stage inflation valves;
- * Double heavy-duty impact-resistant rubber rubbing strake;
- * Looped grab handles on each side of tube;
- * Large molded rubber easy-grip handles on tubes;
- * Repair box

Options:

- * CD stereo system with 2 speakers
- * S/S Roll bar;
- * Steering system including steering wheel, pump and cable
- * International Navigation Lighting;
- * Rule compass A92;
- * Boat cover;
- * S/S swim ladder at transom
- * Teak covering on cockpit deck;
- * Whale Extractable fresh water shower
- * 50L S/S water tank +water system